HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A system for storing checkpoint data state information,

comprising:

a network interface to an external network; and

a persistent memory unit coupled to the network interface, wherein:

the persistent memory unit is configured to receive the checkpoint data into a

region of the persistent memory unit via a remote direct memory write command from a primary

process through the network interface, and to provide access to the checkpoint data in the

region via a remote direct memory read command from [[the]] a backup process through the

network interface, wherein the remote direct memory write command is preceded by a create

request for the region and the read command is preceded by an open request for the region;

and

the backup process provides recovery capability in the event of a failure of the

primary process.

2. (Currently Amended) The system of Claim 1, further comprising:

a persistent memory manager configured to provide address context information to the

network interface and to keep the meta-data on the persistent memory unit consistent with the

checkpoint data stored on the persistent memory unit.

3. (Previously Presented) The system of Claim 1, wherein the persistent memory unit is

configured to provide remote direct memory read access to the checkpoint data to another

processor, and the backup process is executed by the other processor.

HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

4. (Previously Presented) The system of Claim 1, wherein the persistent memory unit

provides the checkpoint data through remote direct memory reads by the backup process after

the primary process fails.

5. (Previously Presented) The system of Claim 1, wherein the persistent memory unit is

configured to store multiple sets of checkpoint data through remote direct memory writes sent

from the processor at successive time intervals.

6. (Previously Presented) The system of Claim 5, wherein the persistent memory unit

provides the multiple sets of checkpoint data through remote direct memory reads upon request

by the backup process at one time.

7. (Previously Presented) The system of Claim 1, wherein the primary process provides

the checkpoint data to the persistent memory unit independently from the backup process.

8. (Original) The system of Claim 1, wherein the persistent memory unit is configured as

part of a remote direct memory access-enabled system area network.

9. (Original) The system of Claim 1, wherein the persistent memory unit is configured

with address protection and translation tables to authenticate requests from remote processors,

and to provide access information to authenticated remote processors.

10. (Previously Presented) A method for recovering the operational state of a primary

process, comprising:

mapping virtual addresses of a persistent memory unit to physical addresses of the

persistent memory;

remote direct memory writing checkpoint data regarding the operational state of the

primary process to the persistent memory unit;

HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

remote direct memory reading the checkpoint data from the persistent memory unit

subsequent to storing access information for the checkpoint data to the physical addresses of

the checkpoint data in the persistent memory unit when the primary process opens a memory

region for the checkpoint data; and

providing the access information to subsequent requestors of the checkpoint data.

11. (Original) The method of Claim 10, further comprising: providing context information

regarding the addresses to the primary process and the backup process.

12. (Previously Presented) The method of Claim 10, further comprising:

remote direct memory reading the checkpoint data by the backup process upon failure of

the primary process.

13. (Original) The method of Claim 10, further comprising:

overwriting the checkpoint data with current checkpoint data.

14. (Previously Presented) The method of Claim 10, further comprising:

appending updated checkpoint data to at least one previous set of the checkpoint data.

15. (Previously Presented) The method of Claim 14, further comprising:

clearing the multiple sets of checkpoint data.

16. (Previously Presented) The method of Claim 14, further comprising:

allowing the backup process to remote direct memory read previously unread portions of

the checkpoint data upon failure of the primary process; and

resuming functions performed by the primary process with the backup process.

17. (Cancelled)

HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

18. (Previously Presented) The method of Claim 10, further comprising:

establishing a connection to a process requesting access to the checkpoint data; and

binding the access information to the connection.

19. (Previously Presented) The method of Claim 10, further comprising:

verifying authentication information from the subsequent requestors.

20. (Original) The method of claim 10, further comprising:

authenticating a persistent memory manager during initialization of address protection

and translation tables on the persistent memory unit.

21. (Previously Presented) A computer product, comprising:

computer executable instructions embodied in a computer readable medium and operable to:

allow remote direct memory access to a persistent memory unit from a remote processor

via a network, wherein the remote direct memory access references a persistent memory virtual

address;

store checkpoint data from a primary process;

authenticate requests from remote processors, and provide access information to

authenticated remote processors based on address protection and translation tables in the

persistent memory unit;

translate the virtual address to a physical address in the persistent memory; and

allow access to the checkpoint data for use in a backup process.

22. (Previously Presented) The computer product of Claim 21, further comprising:

computer executable instructions embodied in a computer readable medium and operable to:

allow the processor to access address context information.

HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

23. (Previously Presented) The computer product of Claim 21, further comprising:

computer executable instructions embodied in a computer readable medium and operable to:

store multiple updates to the checkpoint data sent at successive time intervals.

24. (Previously Presented) The computer product of Claim 21, further comprising:

computer executable instructions operable to:

allow the backup process to access the multiple sets of the checkpoint data at one time.

25. (Original) The computer product of Claim 21, wherein the persistent memory is

configured as part of a remote direct memory access-enabled system area network.

26-31. (Cancelled)

32. (Cancelled)

33. (Currently Amended) The method of Claim [[32]] 34, further comprising:

overwriting the checkpoint data in the persistent memory unit with current checkpoint

data via [[a]] another remote direct memory access write command.

34. (Currently Amended) The method of Claim 32, further A method for recording the

operational state of a primary process, comprising:

appending updated checkpoint data associated with the primary process to a previous

set of the checkpoint data stored in a persistent memory unit via a remote direct memory access

write command; and

receiving access information for physical addresses of checkpoint data in the persistent

memory from the persistent memory unit.

35. (Cancelled)

HP Docket No.: 200312027-1

TKHR Docket No.: 050849-1090

36. (Currently Amended) The method of Claim [[35]] 37, further comprising:

periodically transmitting the remote direct memory access read command to retrieve at

least a portion of the checkpoint data for the backup process.

37. (Currently Amended) The method of Claim 35, further A method for retrieving the

operational state of a primary process, comprising:

transmitting [[the]] a remote direct memory access read command, to a remote

persistent memory unit from a backup process for the primary process, to retrieve previously

unread portions of [[the]] checkpoint data associated with the primary process upon failure of

the primary process; and

receiving access information for physical addresses of the checkpoint data in the

persistent memory from the persistent memory unit.

38. (New) The system of Claim 1, wherein the persistent memory unit is further

configured to store meta-data regarding the contents and layout of memory regions within the

persistent memory unit and to keep the meta-data consistent with the checkpoint data stored on

the persistent memory unit.

39. (New) The system of Claim 1, wherein the persistent memory unit is further

configured to provide access to the checkpoint data in another region via a remote direct

memory read command from the backup process through the network interface, wherein the

read command is preceded by an open request for the another region.